

CKG-12/160,250,400,630 AC High Voltage Vacuum Contactor



► Main Technical Parameter

Type	Rated voltage(V)		Rated current (Main circuit) (A)	Main contact parameter			Power frequency voltage resistance V (effective value)		
	Main circuit	Control circuit		Clearance between open contacts voltage	Overtravel (mm)	Final pressure (N)	Main circuit	Auxiliary circuit	Control circuit
CKG-12/160	12000	110,220,380	160	5 ± 0.5	2 ± 0.2	>85N	42000	2500	2000
CKG-12/250	12000	110,220,380	250	5 ± 0.5	2 ± 0.2	>85N	42000	2500	2000
CKG-12/400	12000	110,220,380	400	5 ± 0.5	2 ± 0.2	>85N	42000	2500	2000
CKG-12/630	12000	110,220,380	630	5 ± 0.5	2 ± 0.2	>85N	42000	2500	2000

Type	Making capacity	Breaking capacity	limit breaking current (A)	Mechanical life times	Weight
CKG-12/160	10le,100 time	8le,25 time	10le	100×10^4	30
CKG-12/250	10le,100 time	8le,25 time	10le	100×10^4	30
CKG-12/400	10le,100 time	8le,25 time	10le	100×10^4	30
CKG-12/630	10le,100 time	8le,25 time	10le	100×10^4	30

Note: le means main circuit rated current

► Overall and installation dimensions

